

TOP
S
P
O



HAEMATOKRIT 210
Hematocrit Centrifuge

HAEMATOKRIT 210

At 16,060 g sedimentation is completed in just a little over 6 minutes.

At any rate, a run time of 10 minutes is sufficient. The rotor comes to a braked standstill.

In rotor 2076, each capillary is secured within its own chamber and supported by a holding tray. This holding tray serves to contain glass shards and any leakage should a tube break. It is easy to clean and disposable in the case of glass breakage.

Capillaries, to be used for quantitative buffy coat analysis are centrifuged in the 20-place rotor prior to further analysis.

HAEMATOKRIT 210 control panel (E control panel)



USER-FRIENDLINESS

- Quick-entry keypad
 - Easy-to-read, digital display
 - Display of current parameter values
- Easy entry of the parameters
 - RPM in increments of 100
 - Running time in minutes, max. 99 min

SAFETY

- Lid locking and holding
- Emergency lid lock release
- Motor overheating protection
- Imbalance switch-off
- Standstill indication

Hematocrit rotor, 24-place

for standard capillaries, lid as evaluation disk incl.



Cat. No. 2076

| | | | |
|--------------------------|-------------------------|--------------|-------------------------------|
| capillaries per rotor | 24 standard capillaries | | |
| capillaries, heparinised | basic | mylar-coated | self-sealing and mylar-coated |
| Cat. No. | 2074 | 1072 | 1071 |

| | |
|---------------|------|
| sealing putty | |
| Cat. No. | 2077 |



The holding trays in rotor 2076 are easy to clean and disposable in the case of glass breakage.

Rotor, 20-place

for quantitative buffy coat analysis, with lid (not suited for standard capillaries)



Cat. No. 2056

TECHNOLOGY

HAEMATOKRIT 210

| Hematocrit centrifuge, without rotor | | |
|--------------------------------------|---|---------------|
| Power supply *) | 208–240 V 1 ~ | 100–127 V 1 ~ |
| Frequency | 50–60 Hz | |
| Consumption | 250 VA | 220 VA |
| Emission | EN 55011 group 1, class B, EN 61000-3-2, EN 61000-3-3 | FCC class B |
| Immunity | EN 61000-6-1 | - |
| Max. capacity | 24/20 capillaries | |
| Max. RPM (speed) | 13,000 min ⁻¹ | |
| Max. RCF | 16,060 | |
| Dimensions (HxWxD) | 247 x 275 x 330 | |
| Weight | approx. 10 kg | |
| Cat. No. | 2104 | 2104 – 01 |

*) Other voltages on request.

Andreas Hettich GmbH & Co. KG

Föhrenstr. 12
D - 78532 Tuttlingen
Germany

www.hettichlab.com
info@hettichlab.com
service@hettichlab.com

Phone +49 (0)7461 / 705 -0
Fax +49 (0)7461 / 705 -122

National Sales: -200
International Sales: -201
National Service: -202
International Service: -203